



ARAT L

Discretion meets elegance. Practicality meets style. 40 different sizes for total versatility, with a heat kick that belies its subtle appearance. Ideal for when wall space is at a premium.

Model shown on opposite page: ARL16-6650-P (polished)

ARAT L

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50	E: Electric only		Finish S: Brushed Matt P: Polished
							Choice of Elements (Watts)		
ARL865	660	390	40	E/H/D	8	1551 454	300	400	S,P
ARL1065	660	490	40	E/H/D	10	1899 556	400		S,P
ARL1265	660	590	40	E/H/D	12	2247 658	400		S,P
ARL1465	660	690	40	E/H/D	14	2596 760	400		S,P
ARL1665	660	790	40	E/H/D	16	2944 862	2x400		S,P
ARL2065	660	990	40	E/H/D	20	3641 1066	2x400		S,P
ARL2465	660	1190	40	H	24	4338 1270	H: Central Heating Only		S,P
ARL2865	660	1390	40	H	28	5427 1589	H: Central Heating Only		S,P
ARL3265	660	1590	40	H	32	5731 1678	H: Central Heating Only		S,P
ARL3665	660	1790	40	H	36	6428 1882	H: Central Heating Only		S,P
ARL4065	660	1990	40	H	40	7125 2086	H: Central Heating Only		S,P
ARL876	760	390	40	E/H/D	8	1861 545	300	400	S,P
ARL1076	760	490	40	E/H/D	10	2279 667	400		S,P
ARL1276	760	590	40	E/H/D	12	2697 790	400		S,P
ARL1476	760	690	40	E/H/D	14	3115 912	400		S,P
ARL1676	760	790	40	E/H/D	16	3533 1034	2x400		S,P
ARL2076	760	990	40	E/H/D	20	4369 1279	2x400		S,P
ARL2476	760	1190	40	H	24	5205 1524	H: Central Heating Only		S,P
ARL2876	760	1390	40	H	28	6513 1907	H: Central Heating Only		S,P
ARL3276	760	1590	40	H	32	6878 2014	H: Central Heating Only		S,P
ARL3676	760	1790	40	H	36	7714 2258	H: Central Heating Only		S,P
ARL4076	760	1990	40	H	40	8550 2503	H: Central Heating Only		S,P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

Call us on 01908 271155 or visit www.aeon.uk.com