



BOLERO

Reminiscent of its passionate Latino namesake. Contemporary design blends bold, angular columns with curvaceous tubular bars. Perfect marriage of performance and beauty.

Model shown on opposite page: BOL2-S (brushed matt) Above: BOL3-S (brushed matt)

BOLERO

SS MATERIAL
10 WORKING PRESSURE
120°C WORKING TEMP.
O C OPEN/CLOSED SYSTEM
V MOUNT POSITION
20 YEARS WARRANTY

| Product Name | Height (mm) | Length (mm) | Depth (mm) | Fuel Options (E/H/D) | Towel Gaps | Pipes or Sections | Heat Output (BTU/w) ΔT 50 | | E: Electric only Choice of Elements (Watts) | | Finish S: Brushed Matt P: Polished |
|--------------|-------------|-------------|------------|----------------------|------------|-------------------|---------------------------|------|--|-----|--|
| | | | | | | | 7 | 9 | 300 | 400 | |
| BOL1 | 630 | 300 | 150 | E/H/D | 1 | 10 | 1794 | 526 | 300 | 400 | S, P |
| BOL2 | 1060 | 300 | 150 | E/H/D | 2 | 16 | 3311 | 971 | 400 | 600 | S, P |
| BOL3 | 1500 | 300 | 150 | E/H/D | 3 | 22 | 4839 | 1419 | 600 | 900 | S, P |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

