

## Spatial economy

A new design that provides a high output for a limited wall space. Tilbrook is ideal for places such as kitchens and narrow areas.

Available in white.

MODEL SHOWN: TS1806W

### TILBROOK

RAL 9016

10

95°C

C

V

5 YEARS

WHITE

WORKING PRESSURE

WORKING TEMP.

CLOSED SYSTEM

MOUNT POS.

WARRANTY

Product Name	Height mm	Length mm	Depth mm	Pipe Centres mm	Wall to Pipe Centre mm	Wall to Face mm	Water Content lt	Gross Weight kg	Fuel Options E/H/D	Heat Output $\Delta T$ 50	
										BTU	Watts
TS1504	1500	106	75	50-196	45	102	1.8	9.2	H	1527	447
TS1506	1500	156	75	50-246	45	102	2.7	13.0	H	2291	671
TS1508	1500	206	75	50-296	45	102	3.7	16.9	H	3053	894
TS1510	1500	256	75	50-346	45	102	4.6	20.7	E/H/D	3818	1118
TS1512	1500	306	75	50-396	45	102	5.5	24.6	E/H/D	4583	1342
TS1514	1500	356	75	50-446	45	102	6.4	28.5	E/H/D	5344	1565
TS1516	1500	406	75	50-496	45	102	7.3	32.3	E/H/D	6109	1789
TS1518	1500	456	75	50-546	45	102	8.3	36.2	E/H/D	6871	2012
TS1520	1500	506	75	50-596	45	102	9.2	40.2	E/H/D	7636	2236
TS1804	1800	106	75	50-196	45	102	2.2	11.0	H	1830	536
TS1806	1800	156	75	50-246	45	102	3.3	15.6	H	2746	804
TS1808	1800	206	75	50-296	45	102	4.3	20.8	H	3661	1072
TS1810	1800	256	75	50-346	45	102	5.4	26.0	E/H/D	4580	1341
TS1812	1800	306	75	50-396	45	102	6.5	29.5	E/H/D	5495	1609
TS1814	1800	356	75	50-446	45	102	7.6	34.4	E/H/D	6410	1877
TS1816	1800	406	75	50-496	45	102	8.7	38.7	E/H/D	7325	2145
TS1818	1800	456	75	50-546	45	102	9.8	43.3	E/H/D	8240	2413
TS1820	1800	506	75	50-596	45	102	10.9	48.1	E/H/D	9156	2681
TS2006	2000	156	75	50-246	45	102	3.6	17.2	H	3053	894
TS2008	2000	206	75	50-296	45	102	4.8	22.3	H	4071	1192
TS2010	2000	256	75	50-346	45	102	6.0	27.9	E/H/D	5088	1490
TS2012	2000	306	75	50-396	45	102	7.2	33.5	E/H/D	6106	1788
TS2014	2000	356	75	50-446	45	102	8.4	37.7	E/H/D	7120	2085
TS2016	2000	406	75	50-496	45	102	9.6	43.1	E/H/D	8138	2383
TS2018	2000	456	75	50-546	45	102	10.8	47.9	E/H/D	9156	2681
TS2020	2000	506	75	50-596	45	102	12.0	53.0	E/H/D	10173	2979



