



PANACEA BATH

The perfect bathroom accessory. This chic, louvre-style towel rail will keep the room toasty while you bathe and give you something lovely to look at while you are getting dressed afterwards.

T Model shown on opposite page: PANB1208-S (brushed matt)

PANACEA BATH

SS MATERIAL
8 WORKING PRESSURE
120°C WORKING TEMP.
O C OPEN/CLOSED SYSTEM
V MOUNT POSITION
20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Towel Gaps	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only Choice of Elements (Watts)		Finish S: Brushed Matt P: Polished
PANB704	660	400	75	E/H/D	1	11	1104	323	300		S, P
PANB1004	985	400	75	E/H/D	2	16	1596	467	300		S, P
PANB1204	1175	400	75	E/H/D	3	18	1813	531	400		S, P
PANB1504	1500	400	75	E/H/D	4	22	2229	653	400		S, P
PANB1704	1680	400	75	E/H/D	4	26	2594	759	400		S, P
PANB705	660	500	75	E/H/D	1	11	1298	380	400		S, P
PANB1005	985	500	75	E/H/D	2	16	1878	550	400		S, P
PANB1205	1175	500	75	E/H/D	3	18	2131	624	400		S, P
PANB1505	1500	500	75	E/H/D	4	22	2617	766	600		S, P
PANB1705	1680	500	75	E/H/D	4	26	3053	894	600		S, P
PANB706	660	600	75	E/H/D	1	11	1493	437	400	600	S, P
PANB1006	985	600	75	E/H/D	2	16	2161	633	400	600	S, P
PANB1206	1175	600	75	E/H/D	3	18	2449	717	600		S, P
PANB1506	1500	600	75	E/H/D	4	22	3006	880	600	900	S, P
PANB1706	1680	600	75	E/H/D	4	26	3512	1028	600	900	S, P
PANB708	660	800	75	E/H/D	1	11	1881	551	400		S, P
PANB1008	985	800	75	E/H/D	2	16	2726	798	400		S, P
PANB1208	1175	800	75	E/H/D	3	18	3085	903	600		S, P
PANB1508	1500	800	75	E/H/D	4	22	3783	1108	600	900	S, P
PANB1708	1680	800	75	E/H/D	4	26	4431	1297	600	900	S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)