



RENDE

Reach for the sky. Echoes of the New York skyline are present in this dramatic super-size radiator. Modern art meets up-to-the minute technology as this exciting heat source steps into the limelight.

Model shown on opposite page: RENV520

RENDE					10 ING PRESSURE	120°C WORKING TEMP	P. OPEN/CLC	SED SYSTEM	V H MOUNT POSITION	20 YEARS WARRANTY	
Product	Height	Length	Depth	Fuel	Pipes	Heat Output		E: Elec	tric only	Finish	
Name	(mm)	(mm)	(mm)	Options (E/H/D)	or Sections	(BTU/w) ΔT 50		Choice of Elements (Watts)		S: Brushed Matt P: Polished	
RENV518	1800	560	33	E/H/D	11	2367	693	600	900	S	
RENV520	2000	560	33	E/H/D	11	2606	763	600	900	S	
RENH518	1800	560	33	E/H/D	27	2261	662	600	900	S	
RENH520	2000	560	33	E/H/D	27	2489	729	600	900	S	
RENTB50 (Towel Bar)	80	560	100							S	

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

