



## DALYA

Squaring the circle. The clever combination of square sections with hollow tubular centres makes this radiator easy to incorporate into any design theme. An attractive way to keep out the cold.

**i** Model shown on opposite page: DAE1466-S (brushed matt) Above left: DAL876-S (brushed matt)

### DALYA E

SS MATERIAL
10 WORKING PRESSURE
120°C WORKING TEMP.
O C OPEN/CLOSED SYSTEM
V MOUNT POSITION
20 YEARS WARRANTY

| Product Name | Height (mm) | Length (mm) | Depth (mm) | Fuel Options (E/H/D) | Pipes or Sections | Heat Output (BTU/w) ΔT 50 |      | E: Electric only<br>Choice of Elements (Watts) |     | Finish<br>S: Brushed Matt<br>P: Polished |
|--------------|-------------|-------------|------------|----------------------|-------------------|---------------------------|------|--|-----|--|
|              |             |             |            |                      |                   |                           |      |  |     |  |
| DAE866       | 600         | 390         | 70         | E/H/D                | 16                | 2582                      | 756  | 300  |     | S, P                                     |
| DAE1066      | 600         | 490         | 70         | E/H/D                | 20                | 3245                      | 950  | 300  |     | S, P                                     |
| DAE1266      | 600         | 590         | 70         | E/H/D                | 24                | 3894                      | 1140 | 400  |     | S, P                                     |
| DAE1466      | 600         | 690         | 70         | E/H/D                | 28                | 4543                      | 1330 | 2x300  | 400 | S, P                                     |
| DAE1666      | 600         | 790         | 70         | E/H/D                | 32                | 5192                      | 1520 | 600  |     | S, P                                     |
| DAE2066      | 600         | 990         | 70         | E/H/D                | 40                | 6490                      | 1900 | 600  |     | S, P                                     |
| DAE2466      | 600         | 1190        | 70         | H                    | 48                | 7788                      | 2280 | H: Central Heating Only                        |     | S, P                                     |
| DAE2866      | 600         | 1390        | 70         | H                    | 56                | 9085                      | 2660 | H: Central Heating Only                        |     | S, P                                     |
| DAE3266      | 600         | 1590        | 70         | H                    | 64                | 10383                     | 3040 | H: Central Heating Only                        |     | S, P                                     |
| DAE3666      | 600         | 1790        | 70         | H                    | 72                | 11681                     | 3420 | H: Central Heating Only                        |     | S, P                                     |

### DALYA L

|          |      |      |    |       |    |      |      |                         |     |      |
|----------|------|------|----|-------|----|------|------|-------------------------|-----|------|
| DAL876   | 760  | 390  | 70 | E/H/D | 16 | 2661 | 779  | 300                     |     | S, P |
| DAL1076  | 760  | 490  | 70 | E/H/D | 20 | 3310 | 969  | 300                     |     | S, P |
| DAL1276  | 760  | 590  | 70 | E/H/D | 24 | 3959 | 1159 | 400                     |     | S, P |
| DAL1476  | 760  | 690  | 70 | E/H/D | 28 | 4608 | 1349 | 2x300                   | 400 | S, P |
| DAL1676  | 760  | 790  | 70 | E/H/D | 32 | 5257 | 1539 | 600                     |     | S, P |
| DAL2076  | 760  | 990  | 70 | E/H/D | 20 | 6555 | 1919 | 600                     |     | S, P |
| DAL2476  | 760  | 1190 | 70 | H     | 48 | 7852 | 2299 | H: Central Heating Only |     | S, P |
| DAL71513 | 1500 | 340  | 60 | H     | 14 | 5127 | 1501 | H: Central Heating Only |     | S, P |
| DAL51816 | 1800 | 240  | 60 | H     | 10 | 4533 | 1327 | H: Central Heating Only |     | S, P |
| DAL61816 | 1800 | 290  | 60 | H     | 12 | 5393 | 1579 | H: Central Heating Only |     | S, P |
| DAL52018 | 2000 | 240  | 60 | H     | 10 | 5072 | 1485 | H: Central Heating Only |     | S, P |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)