



BOMBE

Star quality. The convex and concave curves of this striking design allows light to bounce off its surfaces, creating a vision in heated aluminium perfection. A force to be reckoned with.

Model shown: Opposite page: BLU1806-MA (matt anodised)

BOMBE

AL MATERIAL
 8 WORKING PRESSURE
 95°C WORKING TEMP.
 C CLOSED SYSTEM
 H MOUNT POSITION
 10 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50	
BLU607	600	485	62	H	7	2104	616
BLU609	600	625	62	H	9	2705	792
BLU611	600	765	62	H	11	3306	968
BLU613	600	905	62	H	13	3907	1144
BLU614	600	975	62	H	14	4207	1232
BLU615	600	1045	62	H	15	4508	1320
BLU618	600	1255	62	H	18	5409	1584
BLU621	600	1465	62	H	21	6311	1848
BLU625	600	1745	62	H	25	7513	2200
BLU628	600	1955	62	H	28	8415	2464

MOUNT POSITION

BLU1505	1500	345	62	H	5	3087	904
BLU1507	1500	485	62	H	7	4320	1265
BLU1509	1500	625	62	H	9	5553	1626
BLU1510	1500	695	62	H	10	6171	1807
BLU1803	1800	205	62	H	3	2418	708
BLU1804	1800	275	62	H	4	3224	944
BLU1805	1800	345	62	H	5	4030	1180
BLU1806	1800	415	62	H	6	4836	1416
BLU1807	1800	485	62	H	7	5642	1652
BLU1809	1800	625	62	H	9	7253	2124
BLU2005	2000	345	62	H	5	4559	1335
BLU2007	2000	485	62	H	7	6383	1869
BLU2009	2000	625	62	H	9	8206	2403